


South Timbalier I & II

Gulf of Mexico 3D

215	214	213	212	196	195	194	193	192	191	190	189	188	187	186	185	184
232	233	234	235	197	198	199	200	201	202	203	204	205	206	207	208	209
239	238	237	236	215	214	213	212	211	221	222	223	224	225	226	227	228
256	257	258	259	216	217	218	219	220	238	237	236	235	234	233	232	231
263	262	261	260	243	242	241	240	239	<i>South Timbalier South</i>							
280	281	282	283	244	245	246	247	248	249	250	251	252	253	254	255	256
287	286	285	284	271	270	269	268	267	266	265	264	263	262	261	260	259
304	305	306	307	272	273	274	275	276	277	278	279	280	281	282	283	284
311	310	309	308	299	298	297	296	295	294	293	292	291	290	289	288	287
328	329	330	331	300	301	302	303	304	305	306	307	826	827		308	
335	334	333	332	315	314	313	312	311	310	309	869	870	871	872	873	
352	353	354	355	316	317	318	319	320	911	912	913	914	915	916	917	



NARROW-AZIMUTH 3D STREAMER DATA

Multiclient Services

For more details call:
713 689 1000

www.multiclient.westerngeco.com



South Timbalier I & II

Acquisition Parameters

Recording System	Digital 24-bit
Line Orientation	E/W
Energy Source	109 bar-m
Cable Length	4800 m
Line Spacing	40 m
Nominal Fold	48
Record Length	9 s
Survey Completed	Phase I - October 1994 Phase II - December 1994

Processing Flow

Record length: 9s
Phase II - statics
3D DMO
3D time migration
Final cell size: 12.5 x 20 m